

Multiple Position Fuse Blocks

ATO® Fuse Blocks with Common Feed



Multi-position black thermoplastic fuse block for ATO® fuses. Contacts are recessed for additional safety and a recession in the center of the block accepts a label.

- Common hot feed – stud terminal is 10-32 with hexnut, flat washer and lockwasher
- Blade terminals are .25" wide (6.4mm)
- Four .218" (5.5mm) diameter mounting holes take #10 screws
- Size: 3.375" wide x .812" high (85.7 x 20.6mm)
- Mounting holes 1.06" (27.0mm) on centers, widthwise.

Download additional technical information at: littelfuse.com/Fuseholders

3

PART NUMBERS			VOLTAGE	MAX CONTINUOUS CURRENT	MAX FUSE RATING PER CIRCUIT	NUMBER FUSE LOCATIONS	DIMENSIONS	MOUNTING HOLES ON CENTERS
BULK	BOXED	RETAIL						
46377-6	-BX	-BP	12-24V DC	150A	25A	6	2.47"L x 3.375"W x .812"H	.625"
46377-8	-BX	-	12-24V DC	150A	25A	8	3.09"L x 3.375"W x .812"H	1.25"
46377-10	-BX	-BP	12-24V DC	150A	25A	10	3.72"L x 3.375"W x .812"H	1.875"
46377-12	-BX	-	12-24V DC	150A	25A	12	4.34"L x 3.375"W x .812"H	2.5"
46377-18	-BX	-	12-24V DC	150A	25A	18	6.22"L x 3.375"W x .812"H	4.375"
46379-6	-BX	-	12-24V DC	150A	25A	6	-	-
46379-8	-BX	-	12-24V DC	150A	25A	8	-	-

ATO® Fuse Blocks with 1/4" Quick Connect Terminals



Use with ATO® fuses up to 15 amps. Available in 5 pole unit with removable clear protective cover. Available in side or bottom positioned 1/4" Q.C. terminal configurations. Unit with bottom Q.C. terminals includes detachable side mounting brackets.

Download additional technical information at: littelfuse.com/Fuseholders

PART NUMBERS			DETAILS	AMPERAGE	PROTECTIVE COVER
BULK PART NUMBER 10-PC	CARDED MATERIAL NUMBER	CATALOG NUMBER			
03500417TXN	03500417XP	350417BP	¼" Q.C. side position	2-20A	•
03500418TXN	03500418XP	350418BP	¼" Q.C. bottom position (includes mounting brackets)	25-30A	•

Omni-Blok® Fuse Blocks with 1/4" Quick Connect Terminals



For 1/4" x 1-1/4" glass fuses. Available in one through twelve pole units. Units may be easily broken apart as needed to obtain the desired number of poles. Rated at 20A, 300 V. 354XXX = bulk, OMN = carded.

Download additional technical information at: littelfuse.com/Fuseholders

PART NUMBERS					PART NUMBERS				
BULK	CARDED	POLES	VOLTAGE	AMP	BULK	CARDED	POLES	VOLTAGE	AMP
03540801ZXGY	-	1	300V	20A	354807-GY	-	7	300V	20A
03540802ZXGY	00MN0002XP	2	300V	20A	354808-GY	-	8	300V	20A
03540803ZXGY	-	3	300V	20A	354809-GY	-	9	300V	20A
03540804ZXGY	00MN0004XP	4	300V	20A	354810-GY	-	10	300V	20A
03540805ZXGY	-	5	300V	20A	354811-GY	-	11	300V	20A
03540806ZXGY	-	6	300V	20A	354812-GY	-	12	300V	20A