HBL503NM

By Hubbell Wiring Device-Kellems Catalog ID: HBL503NM



By Hubbell Wiring Device-Kellems

Catalog ID: HBL503NM

Locking Devices, Twist-Lock[®], Marine Grade, Shore Power Inlet, 50A 125V, 2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, White

- New quick connect with backwards compatibility
- Self-closing Friction Tight Cover
- Neoprene gasket on underside of cover for sealing
- Rear enclosure is nickel plated for corrossion resistance

Product Details

Gonoral

o cherar	
Application	Marine Wiring Devices
Color	White

5/2021	HBL503NM Hubbell
Environmental Conditions	Watertight
Insulation	Insulated Body
Item Type	Hull Mount Single
Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Performance	Environmental - Moisture Resistance - IP55 Suitability
Temperature Rating	Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact
UPC	783585519487
Dimensions	
Display Size	Standard Sized Product

Electrical Ratings

15/2021	HBL503NM Hubbell
Amperage Rating	50 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	50 A
Current Rating	50 A
Dielectric Strength	Withstands 3000V Minimum in
Phase	Single Phase
Voltage Rating	125 VAC
Wattage	6250
Conductor Related	
Number Of Wires	3-Wire Grounding
Wire Size	#6 AWG
Certifications and Compliance	
Industry Standard(s)	UL Listed

Non-NEMA

Logistics

Carton Quantity